

6500SS Cooler

Stainless Steel Water Cooler

TW
COOLING SYSTEMS



Rugged & Reliable

Closed-loop design with radiator

reduces coolant temperatures and prevents the system from overheating. It also recirculates the coolant through a fan-cooled heat exchanger

Rustproof coolant reservoir molded of stainless steel for durability and corrosion resistance.

Positive vane-style displacement pumps provide consistent coolant flow and pressure rating with long pump-life expectancy.

Factory-preset pressure-relief valves (60 PSI) maintain consistent pressure during operation.

Thermally protected 1/3 HP motor guards against motor damage due to overheating.

Standard inlet/outlet torch fittings are compatible with TIG and MIG torches having standard 5/8"-18 left-hand fittings.

10ft (3m) power cords with plugs are longer than most power cords in the industry —providing the extra length when required.

Works best with Industrial Supreme

Coolant/Antifreeze and are ideal for warm and cold weather conditions, while providing HF (high frequency) or corrosion protection.



SPECIFICATIONS

Dimensions	21.25" x 13.13" x 20.75" (54.0cm x 33.3cm x 52.7cm)
Reservoir	6 gallon (22.7L) capacity, stainless steel
Pump Capacity	100 psi max. 1.7 GPM (6.4 lpm)
Heat Exchanger	High efficiency, copper core, rustproof
Motor Voltage	6500SS 115V; 6502SS 230V
Amperage	6500SS 6.4/5.6; 6502SS 3.2/2.8
Water Connections	1/4" N.P.T. Connection (supplied with 5/8"-18 UNF LH thread fittings)
Net Weight	43 lbs (19.5 kg)
Shipping Weight	50 lbs (22.7 kg)

MODEL SELECTION CHART

Model	BTU/H	Gallons	Volts	Amps	Hz	Phase
6500SS	14,500	6 (22.7L)	115	6.4/5.6	50/60	Single
6502SS	14,500	6 (22.7L)	230	3.2/2.8	50/60	Single